

COLDROOMS

MINI



Address: **BRATŘI HORÁKOVÉ s.r.o.**,
Mělnická 150, 277 06 Lužec nad Vltavou
Czech republic
<http://www.horak-bros.com>

fax: +420/315619999
☎: +420/315619111
E-mail: export@horak-bros.com

The HORAK MINI range of walk-in refrigerators and freezers covers 5 standard dimensions with volumes of 3 - 6 m³. The MINI range is suitable for catering, shops, households - wherever the storage of refrigerated or frozen products is required. MINI-P models are designed for the storage of various products in the positive temperature range, models MINI-N for storage of frozen items.

INSULATION CABINETS. Cabinets are assembled from sandwich insulation panels and corner elements. The insulation core of the panels is made of rigid polyurethane foam (PUR) that meets today's high standards for environmental protection. The insulation thickness used is 75 mm, door leaf thickness is 80 mm. The panel surface is made of galvanised white lacquered steel plate. A special connecting groove-and-feather system with eccentric locks allows precise and rapid assembly, secures the lasting strength and rigidity of the insulation case and allows eventual dismantling. MINI-N models are, as a standard feature, equipped with heated pressure equalisation valves. The polyurethane panel floor is covered by a pressure-distribution layer and with a non-slip finish, suitable for manual handling of goods. The load allowed is 3000 kg/m².

DOORS. The MINI line is, as a standard feature equipped with left hinged doors 650x1800 mm. Also as a standard feature all models of our doors are equipped with safety opening devices from the inner side. Heating of the contact area between the wings and frame ensures problem-free opening of MINI-N.

REFRIGERATION UNITS. MINI cabinets are, upon request, completed with ZANOTTI monoblocks, roof or wall mounted. Units are equipped with an electronic control panel with an internal temperature gauge. All functions of the units are fully automatic including defrosting, condensate collection and evaporation. Therefore in normal conditions, units don't need any waste disposal connections. Lighting is an integral part of the monoblock unit. Units should be connected to a 230V/50Hz network with 16A fuses, MINI-N with roof units require 20A fuses.

SHELVING SYSTEM. As an option, MINI cabinets can be equipped with a shelving system in stainless steel or anodised aluminium. Standard depth of the shelves is 440 mm.

PACKAGING AND ASSEMBLY. The insulated case is supplied dismantled on a transportation palette. Insulation panels are protected during the transport and assembly by protective foil. The only requirements for MINI cabinet installations are a flat floor and an electrical socket. It is possible to build MINI's in rooms of a minimum height of 2230 mm, or. approx. 2700 mm if you choose the ZANOTTI roof monoblock unit. Depth of wall-mounted monoblocks is 310 mm.

DIMENSIONS*

Type	Int. volume [m ³]	Ext. dimension l x w x h [mm]
MINI 3000	3,0	1150 x 1650 x 2150
MINI 4000	4,0	1150 x 2150 x 2150
MINI 4500	4,5	1650 x 1650 x 2150
MINI 5000	5,0	1150 x 2650 x 2150
MINI 6000	6,0	1650 x 2150 x 2150

- Without monoblock, width means dimension of the wall with doors.
Internal height of MINI cabinets is 2000 mm.

For further information please contact:

Export Department
Mr. Vladimir Hezina
Mr. Eugen Garai
Tel. +420 315 619 / 104, 110
Mob. +420 606 600 536
Fax +420 315 619 999

The manufacturer reserves the right to modify technical features without notice.

Address: BRATŘI HORÁKOVÉ s.r.o.,
Mělnická 150, 277 06 Lužec nad Vltavou
Czech republic
<http://www.horak-bros.com>

fax: +420/315619999
☎: +420/315619111
E-mail: export@horak-bros.com