







## Price list - ZC BLAST CHILLER

SCHOCK COOLING DEVICE - SPLIT CONDENSING UNIT MODELS

Model	Capacity **	Output * +70°C=>+3°C during 90 min	Configuration	
			external dimensions	interior / exterior
<b>ZC 70A</b>	 <p>20x GC 1/1</p> <p>external w x l x h [mm]: 1000x1150x2100 xx)</p> <p>internal effective w x l [mm]: 850/450</p> <p>1pc door 650x1850</p>	70 kg	WHITE LACQUERED/ WHITE LACQUERED	upon request
			INOX / WHITE LACQUERED	upon request
<b>ZC 70</b>	 <p>20x GC 1/1</p> <p>external w x l x h [mm]: 1650x1000x2100 xx)</p> <p>internal effective w x l [mm]: 900/850</p> <p>1pc door 800x1850</p>	70 kg	WHITE LACQUERED / WHITE LACQUERED	upon request
			INOX / WHITE LACQUERED	upon request
<b>ZC 140A</b>	 <p>40x GC 1/1</p> <p>external w x l x h [mm]: 1650x1150x2100</p> <p>internal w x l [mm]: 1000/900</p> <p>1pc door 800x1850</p>	140 kg	WHITE LACQUERED / WHITE LACQUERED	upon request
			INOX / WHITE LACQUERED	upon request
<b>ZC 140</b>	 <p>40x GC 1/1</p> <p>external w x l x h [mm]: 2150x1650x2100</p> <p>internal effective w x l [mm]: 1050/1500</p> <p>1pc door 800x1850</p>	140 kg	WHITE LACQUERED / WHITE LACQUERED	upon request
			INOX / WHITE LACQUERED	upon request
<b>ZC 210</b>	 <p>60x GC 1/1</p> <p>external w x l x v [mm]: 2150x2150x2100</p> <p>internal effective w x l [mm]: 1050/2000</p> <p>1pc door 800x1850</p>	210 kg	WHITE LACQUERED / WHITE LACQUERED	upon request
			INOX / WHITE LACQUERED	upon request

**ZC 280****80x GC 1/1****280 kg**WHITE LACQUERED /  
WHITE LACQUEREDexternal w x l x h [mm]:  
2150x3150x2100

internal w x l [mm]: 1050/3000

1pc door 800x1850

INOX / WHITE  
LACQUERED  
INOX / INOXindividual  
quotation

\* Testing food weight / 1 cycle, stowage on uncovered GC containers, layer up to 35 mm.

\*\* Equipment and usage examples of cabinet - containers, trays and grills are not included in the basic price.

Please compare with the total device output in kg/cycle and the trolley dimensions.

**Basic configuration accessories:**

Control panel with the puncture probe (4 programmable cycles: soft, hard chill, freezing, keeping)

Cooling device is without the connecting pipes (pipes price will be calculated upon real consumption).

Insulating cabinet (insulation thickness 75 mm PUR) for all ZC models.

1pc door 650x1850 mm for ZC 70A, 1pc 800x1850 mm for ZC 70, 140A, 140, 210, 280.

Floor configuration: INOX plate over 75 mm PUR, for all ZC models.

xx) Possibility to deliver also with plastic floor surface (20 mm), external box height 2045mm (valid for ZC70A a ZC70)

**Accessories and Optional Equipment:**

Entrance ramp - INOX AISI 304, width 800 mm

upon request

Trolley for 20 pc GC1/1 - INOX

upon request

Trolley for 20 pc GC2/1 - INOX

upon request

Container GC 1/1 - 40mm, INOX, without cover

upon request

Second door (800x1850) for ZC 70-280 - white finish

upon request

Second door (800x1850) for ZC 70-280 - INOX finish

upon request

Lighting for models 70-140 (incl. door switch )

upon request

Cooling air and product core temperature printer

upon request

Connecting pipes for cooling device

upon request

**Prices are in EUR, EXW Lužec nad Vltavou, w/o VAT, transport and assembly.****Prices are valid since 01.04.2018 untill 30.06.2018.**